

MiniWash is a series of compact dispensing systems designed for use with top load or OPL washing machines. The dispensers feature timed mode programming for liquid and dry laundry product applications. Installation is simple and easy using the supplied wall-mounting brackets.

MiniWash provides enclosures that are gasket sealed, providing optimal electronics protection. The units are available in 1 pump single dispenser or 2 and 3-pump dispenser configurations.







MiniWash 300















**Healthcare** 

**Industrial** 

Sport /Fitness



## **MiniWash Series**



## Features & Benefits

- → Delay time programmability
- > Full installation kit included, easy installation
- → Water-tight, robust, plastic case
- → Reliable peristaltic motor
- → Simple Start / Stop Programming
- → Pre-wired for signals and power
- → Pump dosing time 0 10 minutes by manual calibratio
- → Independent pump delay time from 0 to 5 min
- → Lock-out time from 0 to 75 minutes
- Customized labeling available for 2 and 3 product units
- → Optional remove available for Miniwash 100
- Optional low level chemical alarms available.

## **Specifications**

- → Power 110-230VAC, 50/60Hz
- → Power Consumption: 14W
- → Signal input voltage ranges from 20-240VAC
- → Flow Rate: 8oz/ min
- → Fuse: 315mA@250V 5x20
- → Nema 4X degree protection enclosure, Class 2 electrical insulation

## **Equipment Description**

