



Model 20 Compact Sprayer

MODEL # LAVO 969820-B32

OVERVIEW

The Model 20 Compact Sprayer is a low volume hose-end spray applicator for diluting and applying chemicals to any surface up close or at a distance. This unit uses standard city water pressure to draw chemical concentrate from the attached bottle and blend it into the water stream. This accurately diluted solution is then projected through the recessed fan nozzle. Quick disconnect the chemical assembly to rinse.

Key Features

- Accurately dilutes chemical concentrate and applies it as a low volume spray
- Durable! Injector body is machined in the USA, not molded
- Outlasts and outperforms similar molded plastic products
- The stainless steel quick disconnect socket features 6 retaining balls to lock the bottle and injector assembly securely in place
- Quick disconnect the bottle and injector assembly to rinse
- With less than half the flow rate of competing models, you save money
- Light, 32 oz bottle reduces wrist and arm fatigue as well as the risk of repetitive strain injuries
- No moving parts! Venturi action dilutes chemical consistently with precision metering tips
- Great performance with water pressure as low as 20 PSI
- Recessed fan nozzle for protection and fast coverage
- Color-coded lids help identify equipment and chemicals to enhance user safety (blue standard - red, yellow, or green optional)

Includes

- Machined polypropylene injector body
- Fan nozzle with nozzle protector
- Stainless steel quick disconnect plug and 6-ball socket
- 32 oz wide-mouth, polyethylene bottle
- 20 color-coded precision metering tips to set dilution ratios
- Garden hose gun with inlet screen/filter

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack	# 224150
Small Stainless Steel Hose Rack	# 224145

Additional Bottles

Bottle, 32oz (Includes Solid Lid)	# 709082
-----------------------------------	----------

Unit Storage Rack

Compact Foamer/Sprayer Rack, Stainless Steel	# 224301
--	----------



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	20 - 100 PSI
Flow	0.84 GPM @ 40 PSI
Supply Line	1/2"

Nozzle

2520

Dilution Ratio Range

192:1 to 5:1 @ 40 PSI



www.lavosolutions.com | (949) 377-1250